

MMOX-SID-1

SALIDAS PISTA 01:**SALIDA: TABMI DOS (TABMI2)**

ASCIENDA EN RUMBO DE PISTA HASTA D-4.2 VIRE A LA IZQUIERDA Y PROSIGA EN RUMBO 288° EN RADIAL 330° Y D-9.2 VIRE A LA IZQUIERDA E INTERCEPTE EL RADIAL 300° DEL VOR/DME/OAX HACIA EL FIJO TABMI Y CONTINUE EN RUTA ASIGNADA O INSTRUCCIONES DEL ATC.

SALIDA: MAXIL DOS (MAXIL2)

ASCIENDA EN RUMBO DE PISTA HASTA D-4.2 VIRE A LA IZQUIERDA Y PROSIGA EN RUMBO 288° HASTA INTERCEPTAR EL RADIAL 319° DEL VOR/DME/OAX, CONTINUE EN ASCENSO HACIA EL FIJO MAXIL O INSTRUCCIONES DEL ATC.

SALIDA: OAXACA UNO ALFA (OAX1A)

ASCIENDA DIRECTO EN RUMBO DE PISTA HASTA D-4.2, VIRE A LA IZQUIERDA Y PROSIGA EN RUMBO 288°, EN RADIAL 330° Y D-9.2 VIRE A LA IZQUIERDA DENTRO DE 10 NM HACIA EL VOR/DME/OAX EN RADIAL 293° Y ABANDONELO DE ACUERDO A LA (1) ALTITUD MINIMA DE LA RUTA ASIGNADA O INSTRUCCIONES DEL ATC

LAS SALIDAS TABMI DOS, MAXIL DOS, OAXACA UNO ALFA, REQUIEREN UN GRADIENTE MINIMO DE ASCENSO DE 420 FT/NM HASTA ALCANZAR 12000 FT

NOTA:

ESTAS SALIDAS ESTAN SUJETAS A SOLICITUD DEL PILOTO SOLO PARA AERONAVES QUE CUMPLAN CON UN GRADIENTE MINIMO DE ASCENSO DE 420 FT/NM

DEPARTURES RWY 01:**DEPARTURE: TABMI TWO (TABMI2)**

CLIMB ON RUNWAY HEADING TO D-4.2 OAX, TURN LEFT AND PROCEED ON A 288° HEADING AT OAX R-330° AND D-9.2 TURN LEFT TO INTERCEPT OAX R-300° TO TABMI. THEN ON ASSIGNED ROUTE OR ATC INSTRUCTIONS

DEPARTURE: MAXIL TWO (MAXIL2)

CLIMB ON RUNWAY HEADING TO D-4.2 OAX, TURN LEFT AND PROCEED ON A 288° HEADING, INTERCEPT OAX R-319°, CONTINUE CLIMBING TO MAXIL OR ATC INSTRUCTIONS

DEPARTURE: OAXACA ONE ALPHA (OAX1A)

CLIMB ON RUNWAY HEADING TO D-4.2 OAX, TURN LEFT AND PROCEED ON A 288° HEADING, AT OAX R-330° AND D-9.2 TURN LEFT WITHIN 10 NM TO VOR/DME/OAX, INTERCEPT OAX R-293 AND CROSS IT ACCORDING TO THE (1) MINIMUM CROSSING ALTITUDE OR ATC INSTRUCTIONS

THE SID's TABMI TWO, MAXIL TWO, OAXACA ONE ALPHA, REQUIRE A MINIMUM CLIMB GRADIENT OF 420 FT/NM UNTIL CROSSING 12000 FT

REMARK:

THESE SID's ARE SUBJECT TO PILOT REQUEST ONLY FOR AIRCRAFT THAT COMPLY WITH THE MINIMUM CLIMB GRADIENT OF 420 FT/NM.

REGIMEN DE ASCENSO/ CLIMB REGIME

*PDG: PENDIENTE DE DISEÑO DEL PROCEDIMIENTO / PROCEDURE DESIGN GRADIENT

*PDG VEL (GS) KTS	80	100	120	140	160	180	200
6.9% (FT/MIN)	560	700	840	980	1120	1260	1400

(1) ALTITUD MINIMA PARA ABANDONAR EL VOR/DME/OAX:

(1) MINIMUM ALTITUDE TO LEAVE THE VOR/DME/OAX:

A/TO	VER	V-29		11400
A/TO	MTT	V-16	UJ-16	11000
A/TO	IZT	V-3	J-13	10300
A/TO	NUDOS	V-27 E	UJ-39	9900
A/TO	HUX	V-27	UJ-33 UL-308	9800
A/TO	MASAS	V-29	UJ-69	8800
A/TO	ACA	V-3	UJ-16	10000
A/TO	TEQ	V-16-27	J-13	10300
A/TO	CUA		UJ-39	10200
A/TO	PBC		UJ-33 UL-308	9300